



PROFESSIONAL BANK "DS"

CONTENITORI DI SICUREZZA
ANTIRAPINA A VERSAMENTO
RAPIDO

**ANTI HOLD-UP CASH DAY
DEPOSIT SAFES**

Caratteristiche Tecniche

- Ideale per il deposito temporaneo in locali commerciali, negozi, stazioni di servizio e banche di eccedenze di cassa, di ricevute degli incassi e deposito di documenti che vengono depositati in un cassetto dotato di un sistema anti-riescaggio cadendo nella cassaforte (mod. DS19K e mod. DS19E) o nella cassetta interna (mod. DS32K e mod. DS32E).
CERTIFICATO da IMP secondo la norma europea EN 14450-S1



DS32K



Versione E:
**SERRATURA ELETTRONICA
CERTIFICATA EN 1300**
Version E:
**ELECTRONIC LOCK
EN 1300 CERTIFIED**

Technical Characteristics

- Ideal for temporary storage in shops, businesses, restaurant, petrol station and banks of money surplus, control of cash receipts and deposit of documents. The funds are deposited in a hatch equipped with an anti-fishing hopper and dropping into the main safe (mod. DS19K e mod. DS19E) or into the internal security box with key lock (mod. DS32K e mod. DS32E).
CERTIFIED by IMP according to European standard EN 14450-S1*

Sistema di chiusura:

Serratura con chiave a doppia mappa, certificata UNI EN 1300 (**serie K**).

Serratura a combinazione elettronica digitale certificata EN 1300 (**serie E**)

Locking system:

Double-bitted key lock EN 1300 certified (**K series**)

Digital Electronic combination lock EN 1300 certified (**E series**)



CERTIFICATA A
NORMA EUROPEA
UNI EN 14450:18-S1
CERTIFIED TO
EUROPEAN STANDARD
EN 14450:18-S1



DS19E

Art.	Dim. esterne mm.			Dim. interne mm.			Cassetto			Peso	Litri
Code	External dim. mm.			Internal dim. mm.			Drawer			Weight	Volume
	Alt/H	Larg/W	Prof/D	Alt/H	Larg/W	Prof/D	Alt/H	Larg/W	Prof/D	Kg	Lt
Versione K: con chiave doppia mappa Version K: with double-bitted key											
DS19K	489	342	381*	464	330	317	68	210	100	35	50
DS32K	812	419	427*	796	407	336	68	288	100	55	155
Versione E: combinazione elettronica digitale Version E: digital electronic combination lock											
DS19E	489	342	381*	464	330	317	68	210	100	35	50
DS32E	812	419	427*	796	407	336	68	288	100	55	155

*Aggiungere 40 mm per la sporgenza maniglia

*Add 40 mm for the protrusion of the handle